



EST

Chemical Sanitizing Single Rack Dishwasher






FEATURES:

- **■** Energy Star Qualified.
- 40 racks / 160 covers per hour.
- Economical to operate. Uses only 1.09 gallons of water per cycle.
- All stainless steel construction assures long life and years of trouble free operation.
- Top mounted controls include built-in chemical pumps and deliming system that assures proper chemical usage.
- Power drain saves space, eliminates noisy solenoid and external sump. Drains quickly.
- Available for straight or corner applications.
- Integrated scrap tray prevents food soil from entering drain system.
- Auto start/stop makes operation safe and easy.
- Unique sanitizing system provides instant sanitation and eliminates chlorine damage to the machine.



Power drain saves space, eliminates noisy solenoid and external sump. Drains quickly.



Self cleaning pump screen eliminates operator error. Saves service calls.



Unique sanitizing system sanitizer injector is located close to pump, allowing sanitizing to take place immediately. Strategic location eliminates chlorine damage to the machine.



Built-in "Poly Pro"™ scrap accumulator.


















EST

Chemical Sanitizing Single Rack Dishwasher

WARNING: Plumbing connections must be made by a qualified service company who will comply with all available Federal, State, and Local Health, Plumbing and Safety codes.



Specifications:

| MODEL EST | USA | METRIC | | USA | METRIC |
|-----------------------|-----------|-----------|--------------------------|-----------------|-----------|
| WATER CONSUMPTION | | | FRAME DIMENSIONS | | |
| PER RACK | 1.09 GAL. | (4.12L) | DEPTH | 25-3/4" | (65.4cm) |
| PER HOUR | 43.6 GPH | (165 L) | WIDTH | 25-3/4" | (65.4cm) |
| WATER INLET | 1/2" | (1.27cm) | HEIGHT | 55"-56" | (140cm) |
| DRAIN | 2" | (5.1cm) | STANDARD TABLE HEIGHT | 34" | (86cm) |
| OPERATING CYCLE | | | MAXIMUM CLEARANCE HEIGHT | | |
| WASH TIME - SEC. | 45 | 45 | FOR DISHES | 17" | (43.2cm) |
| RINSE TIME - SEC. | 30 | 30 | STANDARD DISHRACK | 1 | 1 |
| DWELL | 15 | 15 | DIMENSIONS | 19-3/4"X19-3/4" | (50X50cm) |
| TOTAL CYCLE | 90 | 90 | WASH PUMP MOTOR HP | 1 | 1 |
| OPERATING CAPACITY | | | | I . | I . |
| RACKS PER HOUR | 40 | 40 | ELECTRICAL RATING | VOLTS | AMPS |
| WASH TANK CAPACITY | 1.09 GAL. | (4.12 L) | | 115 | 16 |
| PUMP CAPACITY | 52 GPM | (197 LPM) | | | |
| OPERATING TEMPERATURE | | | SHIPPING WEIGHT | | |
| REQUIRED | 120°F | (49°C) | APPROXIMATE | 273# | (124 kg) |
| RECOMMENDED | 140°F | (60°C) | | | |

Summary Specifications: Model EST

The Energy Mizer model EST low temperature, chemical sanitizing commercial dishwasher meets UL Electrical and ETL Sanitation (NSF Standard 3) standards WITHOUT the use of BOOSTER or TANK HEATERS. Model EST is constructed entirely of stainless steel. Each unit automatically washes, rinses and sanitizes food service utensils in standard 20" x 20" racks. Unit comes with upper and lower stainless steel wash arms.

Available Models

- EST-AH Straight
 - (17" Maximum clearance height for dishes)
- EST-C Corner
 - (17" Maximum clearance height for dishes)
- EST-AH-T (Straight Tall)
 - (20-1/2" Maximum clearance height for dishes)
- EST-C-T (Corner Tall)
 - (20-1/2" Maximum clearance height for dishes)

Available Options

- Sanitizer Alarm
- Alternative cycle times, 72 Sec, 2 Min, 3 Min
- Stainless Steel Dishtables





