Undercounter Refrigerators

Unique Energy Saving Design



___ FEATURES / BENEFITS =__

■ EFFICIENT REFRIGERATION SYSTEM

M3's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ STAINLESS STEEL CABINET CONSTRUCTION

The Turbo Air M3 model boasts a stainless steel interior and exterior (except inside wall and the back). It guarantees the utmost in cleanliness and long product life. The M3 can add a touch of style to the most refined setting.

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are formed-in-place using high density, CFC free polyurethane insulation.

ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES

MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Hot Gas Condensate System

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN FOOD PRESERVATION

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight	LDH
MUR-28	1	7	1	1/3	6.6	163	271/2 x 30 x 30
MUR-48	2	12	2	1/3	6.5	246	481/4 x 30 x 30
MUR-60	2	16	2	1/3	8.9	282	601/4 x 30 x 30
MUR-72	3	19	3	1/2	9.9	352	725/8 x 30 x 30

^{*} Height does not include 6-1/2" for caster height.

MODEL MUR-28 MUR-48 MUR-60 Exterior Dimension (LxDxH) 271/2x30x30 481/4x30x30 601/4x30x30 Cubic Feet 7 12 16	MUR-72 725/8x30x30
	COMMUNICATION
Cubic Foot	
Cubic Feet 7 12 16	19
Compressor (HP) 1/3 1/3	1/2
# of Shelves 1ea 2ea 2ea	3ea
Net Weight 146 lbs 229 lbs 260 lbs	303 lbs
Voltage (i) NEMA-5-15P (i)115/60/1 (i)115/60/1 (i)115/60/1	①115/60/1
Amp 6.6 A 6.5 A 8.9 A	9.9 A
Cord Length (ft.) 9 9	9
Plug-In NEMA 5-15P NEMA 5-15P NEMA 5-15P	NEMA 5-15P

^{*}Design and specifications subject to change without notice.

■ WARRANTY: 1 Year Labor and Parts Warranty Additional 4 Years Warranty on Compressor

- SELF-CONTAINED SYSTEM
- 5" SWIVEL CASTERS
- 2.5" CASTERS AVAILABLE FOR ALL MODELS (OPTIONAL)
- STAINLESS STEEL BACK SPLASH (OPTIONAL)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS

(unit: inch)

