

# Universal Manufacturing



Intertek  
3029079



Intertek  
3029079

\* CONFORMS TO UL STD. 471  
 \* CERTIFIED TO CSA STD. C22.2 NO.120  
 \* CONFORMS TO NSF/ANSI STD.7



## URCD79

- **CABINET CONSTRUCTION**  
Exterior -Coated steel  
Interior - attractive, aluminum liner with stainless steel floor.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**  
Low-E, double pane, curved frontal glass
- **Refrigeration system:** Gravity coil refrigeration system provides high humidity environment for meats and deli products, which holds 32°F ~43° F
- **Electronic control system:**  
Adjustable temperature set point and defrost frequency  
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath

### Bottom mounted units feature:

- "No stoop" lower shelf.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

### Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

NSF Model	Doors	Shelves	Cabinet Dimensions (inches)			CAP. CU.FT.	HP	Voltage	Amps	NEMA Config.
			L	D	H					
DC200	3	9	78.75	32.5	42.88	32	1/2+	115/60/1	6.3	5-15P 